

COMAG-Engineering-GmbH
Kinskyg. 40-44
A-1230 Vienna
AUSTRIA EUROPE



Vienna - Austria

Machinery + Tools
Tel.: (+43-1-) 662 94 46
Fax: (+43-1-) 662 94 46/90
E-Mail: office@comag.at

®VACO COL 2000



Material Safety Data Sheet According to 91/155 EC

1. Identification of substance

Product details

Trade name: VACO-COL 2000

Articel number: 1317

Manufacturer/Supplier: COMAG Engineering Ges.m.b.H

2. Composition/Data on components:

Chemical characterization

Description: waterbased polyvinylacetate dispersion adhesive

Dangerous components: void

3. Hazards identification

Hazard designation: void

Information pertaining to particular dangers for man and environment: void

Classification system:

The classification is in line with current EC lists.

It is expanded, however, by information from technical literature and by information furnished by supplier companies.

4. Physical and chemical properties:

Form: fluid

Colour: white

Smell: characteristic

Value/Range Unit /Method

Melting point/Melting range: ca. 0°

Boiling opoint/Boiling range: ca. 100°

Flash point: 100°

Danger of explosion: Product is not explosive.

Steam pressure: at 20C 24 h

Pa Density: at 20

ca.: 1,0 g/cm³

Solubility: in water

Miscibility: with water fully miscible

ph-value: slightly acidic

Viscosity: dynamic at 20C ca. 2000 m

Pas BRKLD RVT 3

Solvent content:water: ca. 60 %

Solids content: ca. 40 %